



STRENX®
PERFORMANCE STEEL

- 

Trinciatrice da vigneto e frutteto per erba e sarmenti fino a Ø 4-5 cm., da applicare a trattori con potenza compresa tra 30 e 60 HP.
- 

Broyeur à vignobles et vergers indiqué pour broyer l'herbe, les buissons et les sarments allant jusqu'à Ø 4-5 cm., pour les tracteurs de 30 à 60 CV.
- 

Mulcher for vineyard and orchard, suited to mulch grass, bushes and pruning up to Ø 4-5 cm. For tractors from 30 to 60 HP.
- 

Trituradora para viñedos y frutales. Apta para triturar hierba y material leñoso de hasta 4-5 cm. de diámetro para tractores con una potencia entre 30 y 60 CV.
- 

Gerät für den Wein- und Obstbau, für Traktoren von 30 bis 60 PS. Es eignet sich zum Mulchen von Gras, Büsche und Reisig bis Ø 4-5 cm.

Mod.													
	cm	Min	Max	mm	n°	n°	n°	PTO	A	B	C	min	max
AF 135	130	30	60	715635 3451005 715735	12	36	3	540 (1000)	85	150	100	375	460
AF 145	140	30	60	715735 3451105 715885	14	42	3	540 (1000)	85	160	100	400	480
AF 160	155	30	60	3451255 7151085 3451455	14	42	3	540 (1000)	85	175	100	425	500
AF 180	175	30	60	7151085 3451455	16	48	3	540 (1000)	85	195	100	460	525




- Attacco ai tre punti spostabile meccanicamente, Cat. I.
- Displaceable three point linkage, Cat. I (mechanical).
- Versetzbarer Dreipunktbock, Kat. I (mechanischer).
- Attelage déportable à 3 points, Cat. I (mécanique).
- Enganche a los 3 puntos del tractor desplazable, Cat. I (desplazamiento mecánico).




- Rullo livellatore regolabile Ø 139 con pulirullo.
- Adjustable and levelling roller Ø 139, with scraper.
- Einstellbare Stützwalze Ø 139 mit Abstreifer.
- Rouleau palpeur réglable Ø 139 avec décrotoir.
- Rodillo nivelador Ø 139 con polirodillo.



- Fiancata destra arrotondata e priva di sporgenze.
- Chamfered profile on the right hand side, with no juts.
- Seitliche Abschrägung auf Rahmen, ohne Vorsprünge.
- Coin côté droit arrondi et sans saillies.
- Ángulo costado derecho redondeado y sin salientes.



- PTO 540/1000 g/min (invertendo le pulegge).
- PTO 540/1000 rpm (reversing the pulleys).
- Getriebe 540 oder 1000 U/min (Umkehrbare Riemenscheibe).
- PDF 540/1000 t/min (en inversant les poulies).
- PTO 540/1000 g/min (invirtiendo las poleas).



OPTIONALS



- Spostamento idraulico con tubi e innesti rapidi.
- Hydraulic side shift with hoses and quick couplings.
- Hydraulische Seitenverschiebung.
- Déport hydraulique avec tuyaux et prises rapides.
- Desplazamiento hidráulico.



- Slitte di appoggio.
- Skids.
- Satz Kufen.
- Jeu patins.
- Patines.



- Attacco centrale.
- Centre mounted linkage.
- Mittiger Anbau.
- Attelage axial.
- Enganche central.



- Albero cardanico.
- Pto drive shaft.
- Gelenkwelle.
- Arbre cardan.
- Cardan.

Mod.	
mm	
AF 160	893 707
	520 1080
AF 180	893 907
	520 1280